



## SAFETY RESTRAINTS

### HOSE WHIP STOP RESTRAINTS



**REDUCES THE DANGER OF  
HIGH PRESSURE BLOW OUTS**

**SECURES HOSE DIRECTLY TO  
EQUIPMENT OR PIPE SYSTEMS**

**CAN BE CUSTOM DESIGNED  
TO SUITE MANY APPLICATIONS**

HOSE ID	ITEM NUMBER	HOSE OD RANGE	MAX PSI FLUID	MAX PSI AIR / GAS
3/8"	8-14W/S	0.31" - 0.50"	25,000	12,000
1/2"	14-20W/S	0.51" - 0.75"	14,000	7,000
7/8"	20-30W/S	0.76" - 1.12"	6,500	3,400
1"	30-40W/S	1.13" - 1.50"	8,500	4,200
1-1/4"	40-50W/S	1.51" - 1.87"	5,400	2,700
1-1/2"	50-60W/S	1.88" - 2.37"	6,000	3,000
2"	60-70W/S	2.38" - 2.75"	3,300	1,650
2-1/2"	70-85W/S	2.76" - 3.50"	2,100	1,000
3"	85-100W/S	3.38" - 3.87"	2,400	1,200
3-1/2"	100-120W/S	3.87" - 4.75"	1,800	900
4"	120-140W/S	4.76" - 5.50"	1,500	750
6"	140-180W/S	5.51" - 7.00"	700	350

**HOBBLE CLAMP (SHOWN IN RED) IS NOT INCLUDED AND CAN BE ORDERED IN A VARIETY OF SIZES**

### NYLON HOSE RESTRAINTS



ITEM NUMBER	HOSE ID RANGE*	LENGTH**
HRNC118	1/4" - 1"	18"
HRNC124	1/4" - 1"	24"
HRNC130	1/4" - 1"	30"
HRNC136	1/4" - 1"	36"
HRNC156	1-1/2" - 4"	36"
HRNC180	3" - 6"	36"

ITEM NUMBER	HOSE ID RANGE*	LENGTH**
HRNC218	1/4" - 1"	18"
HRNC224	1/4" - 1"	24"
HRNC236	1-1/2" - 3"	36"
HRNC248	1" - 4"	48"
HRNC260	2-1/2" - 6"	60"

**3 AND 4 PLY VERSIONS AVAILABLE**

**\*LENGTH IS LOOP TO LOOP CENTER, AT MEDIAN HOSE DIAMETER IN THE RANGE**

### HOSE MAXIMUM OPERATING PSI

HOSE ID:	1 PLY AIR / GAS	2 PLY AIR / GAS
1/4"	26,000	40,000
3/8"	12,000	15,000
1/2"	6,500	13,000
3/4"	3,000	6,000
1"	1,700	3,350
1-1/2"	750	1,500

HOSE ID:	1 PLY AIR / GAS	2 PLY AIR / GAS
2"	725	825
2-1/2"	450	535
3"	325	375
4"	175	200
5"	100	125
6"	75	85

**USE WILL REDUCE BUT  
NOT ELIMINATE  
RISK OF INJURY**

**DO NOT USE FOR LIFTING**

**IN OUTDOOR SERVICE:  
REPLACE EVERY 2 YEARS**

**DOUBLE WRAP SIZES THROUGH 1-1/4" TO ACHIEVE MAX PRESSURE RATING  
REFER TO INSTALLATION VIDEO AT [CAPITALRUBBERCORP.COM](http://CAPITALRUBBERCORP.COM)**