

# **SUCTION HOSE**

## **6901-OILFIELD / HI-FLEX SUCTION**

### **ASSEMBLIES WITH MALE & FEMALE CAM LOCK COUPLINGS**



1-1/2" X 20'	6901-150X20CE
2" X 20'	6901-2X20CE
3" X 20'	6901-3X20CE
4" X 20'	6901-4X20CE

*CRIMPED ASSEMBLIES ALSO AVAILABLE*

**HI-FLEX**

### **ASSEMBLIES WITH MALE & FEMALE CAM LOCK COUPLINGS**



1-1/2" X 20'	6901C-150X20CE
2" X 20'	6901C-2X20CE
3" X 20'	6901C-3X20CE
4" X 20'	6901C-4X20CE
6" X 20'	6901C-6X20CE

*CRIMPED ASSEMBLIES ALSO AVAILABLE*

**FORMULATED FOR MAXIMUM FLEXIBILITY AND KINK RESISTANCE**

### **FULL VACUUM RATED HOSE FOR TRANSPORT OF BULK UNREFINED PETROLEUM WASTE, OILY SLUDGE AND SLURRIES**

**FOR FEMALE CAM X MALE NPT END FITTINGS USE \_CN INSTEAD OF \_CE  
FOR 25 FOOT LENGTHS REPLACE X20 FOR X25 IN THE PART NUMBER**

**-20 TO + 180 DEG F**

### **BULK HOSE**

**-20 TO + 180 DEG F**

#### **TYPE 6901**

#### **TYPE 6901C**

SIZE (ID)	ITEM NUMBER	PSI RATING	LBS / FOOT
1.5"	6902-150	150	0.70
2"	6902-200	150	0.95
3"	6902-300	150	1.70
4"	6902-400	150	2.95
<b>6" SIZE AVAILABLE IN HI FLEX ONLY</b>			

SIZE (ID)	ITEM NUMBER	PSI RATING	LBS / FOOT
1.5"	6902C-150	150	1.10
2"	6902C-200	150	1.35
3"	6902C-300	150	2.15
4"	6902C-400	150	3.50
6"	6902C-600	150	4.85

**8" FRAC TANK HOSE ALSO AVAILABLE**

**PSI RATING LISTED IS THE RECOMMENDED MAX OPERATING PRESSURE OF THE BULK HOSE ONLY  
HOSE ASSEMBLY WORKING PRESSURE RATING IS DEPENDENT ON THE COUPLING TYPE**



Pixelated text or header element.

Pixelated text or header element.



Pixelated text block.

Pixelated text or header element.



Pixelated text block.

Pixelated text or header element.

Pixelated text or header element.

Pixelated text or header element.

Pixelated text or header element.

Pixelated text block.

Pixelated text block.

Pixelated text block.