

SUCTION HOSE

7910 – BUMBLE BEE VAC

TYPE 7910

CRUSH-RESISTANT & HIGH FLEX



TYPE 7910S

LIGHTWEIGHT & HIGH FLEX



ASSEMBLIES WITH MALE & FEMALE NPSH THREADED COUPLINGS

1-1/2" X 20'	7910-150X20MF
2" X 20'	7910-2X20MF
3" X 20'	7910-3X20MF
4" X 20'	7910-4X20MF

1-1/2" X 20'	7910S-150X20MF
2" X 20'	7910S-2X20MF
3" X 20'	7910S-3X20MF
4" X 20'	7910S-4X20MF

ASSEMBLIES WITH MALE & FEMALE CAM LOCK COUPLINGS

1-1/2" X 20'	7910-150X20CE
2" X 20'	7910-2X20CE
3" X 20'	7910-3X20CE
4" X 20'	7910-4X20CE

1-1/2" X 20'	7910S-150X20CE
2" X 20'	7910S-2X20CE
3" X 20'	7910S-3X20CE
4" X 20'	7910S-4X20CE

FOR ASSEMBLIES WITH FEMALE CAM X MALE NPT: REPLACE THE CE IN ABOVE PART NUMBER WITH CN
OTHER LENGTHS AVAILABLE BY SPECIAL ORDER UP TO 60 FT MAXIMUM

-40 TO + 150 DEG F

BULK HOSE

-40 TO + 140 DEG F

TYPE 7910

TYPE 7910S

SIZE (ID)	ITEM NUMBER	PSI RATING	LBS / FOOT
1-1/2"	7910-150	20	0.60
2"	7910-200	15	0.85
3"	7910-300	7	1.20
4"	7910-400	7	1.60

SIZE (ID)	ITEM NUMBER	PSI RATING	LBS / FOOT
1-1/2"	7910S-150	20	0.36
2"	7910S-200	14	0.57
3"	7910S-300	12	1.20
4"	7910S-400	10	1.47

ALL BULK HOSE INCLUDES POLYWELDED CUFFS INSTALLED EACH END

THREADED REPLACEMENT CUFFS & GLUE AVAILABLE, CUFFS DO NOT INTERCHANGE BETWEEN STYLES

WORKING PRESSURE & VACUUM RATING DECREASE AS TEMPERATURE INCREASES

RATED FOR FULL VACUUM IN ALL SIZES, NOT RECOMMENDED FOR POSITIVE PRESSURE APPLICATIONS