

SUCTION HOSE

6902 – TANK TRUCK PETROLEUM

ASSEMBLIES WITH MALE & FEMALE CAM LOCK COUPLINGS



1-1/2" X 20'	6902-150X20CE
2" X 20'	6902-2X20CE
2-1/2" X 20'	6902-250X20CE
3" X 20'	6902-3X20CE
4" X 20'	6902-4X20CE
6" X 20'	6902-6X20CE

CRIMPED ASSEMBLIES ALSO AVAILABLE

HI-FLEX

ASSEMBLIES WITH MALE & FEMALE CAM LOCK COUPLINGS



1-1/2" X 20'	6902C-150X20CE
2" X 20'	6902C-2X20CE
2-1/2" X 20'	6902C-250X20CE
3" X 20'	6902C-3X20CE
4" X 20'	6902C-4X20CE
6" X 20'	6902C-6X20CE

CRIMPED ASSEMBLIES ALSO AVAILABLE

SPECIALLY FORMULATED HOSE FOR THE TRANSFER & UNLOADING OF MOST OILS, REFINED FUEL, ETHANOL, GASOLINE, WITH AROMATIC CONTENT UP TO 50 PERCENT BIODIESEL & DIESEL EXHAUST FLUID COMPATIBLE HOSES AVAILABLE, PLEASE INQUIRE

-25 TO + 200 DEG F

SMOOTH COVER

SIZE (ID)	ITEM NUMBER	PSI RATING	LBS / FOOT
1-1/2"	6902-150	150	0.90
2"	6902-200	150	1.15
2-1/2"	6902-250	150	1.80
3"	6902-300	150	2.40
4"	6902-400	150	2.75
6"	6902-600	150	6.25
8"	6902-800	150	7.20

BULK HOSE

-40 TO + 180 DEG F

HI-FLEX COVER

SIZE (ID)	ITEM NUMBER	PSI RATING	LBS / FOOT
1-1/2"	6902C-150	150	0.80
2"	6902C-200	150	1.05
2-1/2"	6902C-250	150	1.35
3"	6902C-300	150	1.60
4"	6902C-400	150	2.50
6"	6902C-600	150	4.25
8"	6902C-800	150	6.20

HIGHER PRESSURE RATING OPTIONS AVAILABLE – RED COVER HOSE AVAILABLE

**PSI RATING LISTED IS THE RECOMMENDED MAX OPERATING PRESSURE OF THE BULK HOSE ONLY
HOSE ASSEMBLY WORKING PRESSURE RATING IS DEPENDENT ON THE COUPLING TYPE**