

SUCTION HOSE

2902C / 2909C – CHEMICAL TRANSFER



316-SS CRIMP COUPLINGS SHOWN

2909C XLPE LINED HOSE

WITH MALE & FEMALE CAM LOCK COUPLINGS
CROSS LINKED POLYETHYLENE TUBE

1" X 20'	2909C-1X20CE
1-1/2" X 20'	2909C-150X20CE
2" X 20'	2909C-2X20CE
2-1/2" X 20'	2909C-250X20CE
3" X 20'	2909C-3X20CE
4" X 20'	2909C-4X20CE

ADD -SS FOR STAINLESS STEEL COUPLINGS
INQUIRE FOR CRIMPED ASSEMBLIES

2902C UHMW PE LINED HOSE

WITH MALE & FEMALE CAM LOCK COUPLINGS
ULTRA HIGH MOLECULAR WEIGHT - PE TUBE

1" X 20'	2902C-1X20CE
1-1/4" X 20'	2902C-125X20CE
1-1/2" X 20'	2902C-150X20CE
2" X 20'	2902C-2X20CE
2-1/2" X 20'	2902C-250X20CE
3" X 20'	2902C-3X20CE
4" X 20'	2902C-4X20CE
6" X 20'	2902C-6X20CE

SPECIALLY FORMULATED POLYETHYLENE TUBE CONVEYS MOST CHEMICALS
CONSULT CHEMICAL RESISTANCE CHARTS AND TEST COMPATABILITY PRIOR TO USE
FEP LINED RUBBER OR STAINLESS BRAIDED COVER HOSE ASSEMBLIES AVAILABLE

XLPE TUBE

BULK HOSE

UHMW-PE TUBE

SIZE (ID)	ITEM NUMBER	PSI RATING	LBS / FOOT
1"	2909C-100	200	0.60
1-1/2"	2909C-150	200	0.85
2"	2909C-200	200	1.20
2-1/2"	2909C-250	200	1.45
3"	2909C-300	200	1.95
4"	2909C-400	200	2.75

UHMW PE HOSE ALSO AVAILABLE IN GREEN COVER

SIZE (ID)	ITEM NUMBER	PSI RATING	LBS / FOOT
1"	2902C-100	200	0.60
1-1/2"	2902C-150	200	0.86
2"	2902C-200	200	1.15
2-1/2"	2902C-250	200	1.45
3"	2902C-300	200	1.80
4"	2902C-400	200	2.85
6"	2902C-600	200	5.60

SAFE TEMPERATURE RATINGS DEPEND ON THE APPLICATION AND CHEMICAL BEING CONVEYED
PSI RATING LISTED IS THE RECOMMENDED MAX OPERATING PRESSURE OF THE BULK HOSE ONLY
HOSE ASSEMBLY WORKING PRESSURE RATING IS DEPENDENT ON THE COUPLING TYPE