

AIR / WATER HOSE

1502 – RED EPDM RUBBER

ASSEMBLIES WITH UNIVERSAL COUPLINGS



SIZE (ID)	ITEM NUMBER	COLOR	PSI RATING*
1/2"	1502-50X50R	RED	300
3/4"	1502-75X50R	RED	300
3/4"	1502M-75X50R	RED	200
3/4"	1502-75X50Y	YLW	300
3/4"	1502-75X50B	BLUE	300
1"	1502-1X50R	RED	300
1"	1502M-1X50R	RED	200

* PRESSURE RATING LISTED ABOVE IS THE HOSE RATING ONLY
ASSEMBLIES WITH UNIVERSAL COUPLINGS ARE RATED AT 150 PSI

ASSEMBLIES WITH M NPT BRASS COUPLINGS



SHOWN WITH OPTIONAL
QUICK CONNECT COUPLINGS

HOSE SIZE (ID)	THREAD SIZE (NPT)	ITEM NUMBER
1/4"	1/4"	1502-25X50MM
3/8"	1/4"	1502-38X50-04M
3/8"	3/8"	1502-38X50-06M
1/2"	1/2"	1502-50X50MM

50 FT ASSEMBLIES LISTED - 25 & 100 FT LENGTHS AVAILABLE

ALWAYS USE SAFETY CABLES TO SECURE AIR HOSE

REELS MAY NOT BE CONTINUOUS

BULK HOSE

-40 TO +212 DEG F



ARPM CLASS C OIL RESISTANT TUBE
(OIL MISTED AIR ACCEPTABLE)

PSI RATING IS FOR THE BULK HOSE ONLY
ASSEMBLY PRESSURE VARIES BASED ON
COUPLING AND CLAMP TYPE

SIZE (ID)	ITEM NUMBER	PSI RATING	LBS / FOOT	FT / REEL
1/4"	1502-25	300	0.12	800
3/8"	1502-38	300	0.16	700
1/2"	1502-50	300	0.25	500
5/8"	1502-63	300	0.35	450
3/4"	1502-75	300	0.38	400
1"	1502-100	300	0.52	300
1-1/4"	1502-125	200	0.80	250
1-1/2"	1502-150	200	0.90	200
2"	1502-200	200	1.20	250

200 PSI VERSION AVAILABLE ALL SIZES