

AIR / WATER HOSE

1503 – NITRILE OIL RESISTANT RUBBER



REELS MAY NOT BE CONTINUOUS

-40 TO +212 DEG F

OIL RESISTANT / NON-CONDUCTIVE

SIZE (ID)	ITEM NUMBER	PSI RATING	LBS / FT	SPOOL LGTH
1/4"	1503-25	300	0.12	800'
3/8"	1503-38	300	0.18	650'
1/2"	1503-50	300	0.26	500'
3/4"	1503-75	300	0.40	400'
1"	1503-100	300	0.56	300'

*NOT FOR REFINED FUEL APPLICATIONS
INQUIRE FOR FUEL & OIL DELIVERY HOSE*

1509 – PUSH LOCK RUBBER



AVAILABLE IN BLACK, BLUE,
RED, GREEN & GRAY
REELS MAY NOT BE CONTINUOUS

-40 TO +212 DEG F

OIL RESISTANT / HIGHLY FLEXIBLE

SIZE (ID)	ITEM NUMBER	PSI RATING	LBS / FT	SPOOL LGTH
1/4"	1509_-25	300	0.10	700'
3/8"	1509_-38	300	0.12	700'
1/2"	1509_-50	300	0.16	600'
5/8"	1509_-63	300	0.22	500'
3/4"	1509_-75	300	0.30	400'

COMPATIBLE WITH B20*, DIESEL, ETHANOL & GASOLINE
(NOT FOR FUEL DISPENSING APPLICATIONS)
*IN DEDICATED SERVICE

PUSH LOCK HOSE COUPLINGS

NO HOSE CLAMP OR FERRULE IS REQUIRED WHEN ASSEMBLING PUSH LOCK HOSE
WITH THESE SPECIALLY DESIGNED PUSH LOCK COUPLINGS

CUT HOSE STRAIGHT AND PRESS FITTING IN COMPLETELY UP TO YELLOW RING



MALE NPT RIGID & SWIVEL
MALE SAE / JIC THREAD
MALE NPT 90° ELBOW



HOSE TO HOSE MENDER
JUMP SIZES AVAILABLE



FEMALE NPSM SWIVEL
FEMALE NPT RIGID
FEMALE SAE / JIC

GARDEN THREAD M & F NOW AVAILABLE

DO NOT USE A CLAMP WITH THESE FITTINGS, THE SPECIAL SERRATIONS WILL CUT INTO THE HOSE WALL