

1803 – WIRE BRAID / BULL AIR

ASSEMBLIES WITH UNIVERSAL QUICK CONNECT COUPLINGS



**ASSEMBLIES WITH UNIVERSAL COUPLINGS
ARE RATED FOR 150 PSI**

3/4" X 50'	1803-75X50UB
1" X 50'	1803-1X50UB
1-1/2" X 50'	1803-150X50UB
2" X 50'	1803-2X50UB

2-LUG COUPLING DESIGN THROUGH 1" HOSE ID
ASSEMBLIES OVER 1" HAVE 4-LUG COUPLING DESIGN
2-LUG AND 4-LUG COUPLINGS ARE NOT COMPATIBLE
25 & 100 FT LENGTHS ALSO AVAILABLE

ASSEMBLIES WITH MALE NPT & FEMALE GROUND JOINT COUPLINGS



**FEMALE GROUND JOINT COUPLING
INCLUDES FEMALE NPT SPUD ADAPTER
DOUBLE SPUD & M NPT SPUD ALSO AVAILABLE**

3/4" X 50'	1803-75X50MFGJ
1" X 50'	1803-1X50MFGJ
1-1/2" X 50'	1803-150X50MFGJ
2" X 50'	1803-2X50MFGJ
3" X 50'	1803-3X50MFGJ
4" X 50'	1803-4X50MFGJ

FEMALE GROUND JOINT EACH END = FFGJ
25 & 100 FT LENGTHS ALSO AVAILABLE

ALWAYS USE SAFETY CABLES TO SECURE AIR HOSE

100 FT MAX ROLL LENGTH

BULK HOSE

-25 TO +200 DEG F

SIZE (ID)	ITEM NUMBER	PSI RATING	LBS / FOOT
1/2"	1803-50	600	0.40
3/4"	1803-75	600	0.65
1"	1803-100	600	0.85
1-1/4"	1803-125	600	1.10
1-1/2"	1803-150	600	1.30

SIZE (ID)	ITEM NUMBER	PSI RATING	LBS / FOOT
2"	1803-200	600	1.90
2-1/2"	1803-250	600	2.50
3"	1803-300	600	3.30
4"	1803-400	600	4.75
6"	1803-600	600	6.89

TEXTILE BRAID VERSION (NO WIRE) ALSO AVAILABLE – TYPE 1801

HIGH-TEMP VERSION (+275 DEG F) AVAILABLE IN SELECT SIZES – TYPE 1803H

HIGH PRESSURE HOSE WHIP RESTRAINTS AVAILABLE

PSI RATING LISTED IS THE RECOMMENDED MAX OPERATING PRESSURE OF THE BULK HOSE ONLY
ASSEMBLY PRESSURE WILL VARY BASED ON SIZE AND FITTING TYPE