

AIR / WATER HOSE

1522 – BLACK EPDM RUBBER

ASSEMBLIES WITH BRASS MXF GHT COUPLINGS



HOT WATER SERVICE APPROVED
STAYES FLEXIBLE IN COLD WEATHER



CRUSH-PROOF HD BRASS COUPLINGS
CUSTOM CONFIGURATIONS AVAILABLE

MD GRADE HOSE IS 125 PSI WITH
NICKLE PLATED BRASS GHT FITTINGS

5/8" HOSE ASSEMBLIES

5/8" X 25'	1522-63X25GHT
5/8" X 50'	1522-63X50GHT
5/8" X 100'	1522-63X100GHT

3/4" HOSE ASSEMBLIES

3/4" X 25'	1522-75X25GHT
3/4" X 50'	1522-75X50GHT
3/4" X 100'	1522-75X100GHT

1" HOSE ASSEMBLIES

1" X 50'	1522-1X50GHT
1" X 50'	1522-1X50MF

MF = NPSH STRAIGHT THREAD

MD GRADE WATER HOSE

5/8" X 50'	1521-63X50GHT
3/4" X 50'	1521-75X50GHT

REELS MAY NOT BE CONTINUOUS

BULK HOSE

-40 TO +212 DEG F



CUT LENGTHS AVAILABLE

PSI RATING IS FOR THE BULK HOSE ONLY
ASSEMBLY PRESSURE VARIES BASED ON
COUPLING AND CLAMP TYPE

SIZE (ID)	ITEM NUMBER	PSI RATING	LBS / FOOT	FT / REEL
1/4"	1522-25	200	0.10	800
3/8"	1522-38	200	0.16	700
1/2"	1522-50	200	0.22	500
5/8"	1522-63	200	0.26	450
3/4"	1522-75	200	0.34	400
1"	1522-100	200	0.45	300
1-1/4"	1522-125	200	0.78	250
1-1/2"	1522-150	200	0.86	200
2"	1522-200	200	1.20	250