

# **DISCHARGE HOSE**

## **7801 – BLUE PVC DISCHARGE**

### **ASSEMBLIES WITH MALE & FEMALE NPSH THREADED COUPLINGS**



1-1/2" X 50'	7801-150X50MF*
2" X 50'	7801-2X50MF
2-1/2" X 50'	7801-250X50MF*
3" X 50'	7801-3X50MF
4" X 50'	7801-4X50MF
6" X 50'	7801-6X50MF

\*SIZES AVAILABLE WITH NST FIRE THREAD  
3/4" & 1" SIZES AVAILABLE WITH HD BRASS MXF

### **ASSEMBLIES WITH CAM LOCK ALUMINUM QUICK CONNECT COUPLINGS**



1-1/2" X 50'	7801-150X50CE
2" X 50'	7801-2X50CE
2-1/2" X 50'	7801-250X50CE
3" X 50'	7801-3X50CE
4" X 50'	7801-4X50CE
6" X 50'	7801-6X50CE

**AVAILABLE WITH BALL & SOCKET COUPLINGS**

**300 FT MAX ROLL LENGTH**

**BULK HOSE**

**-5 TO +170 DEG F**

SIZE (ID)	ITEM NUMBER	PSI RATING	LBS / FOOT
3/4"	7801-075	140	0.08
1"	7801-100	110	0.11
1-1/4"	7801-125	80	0.14
1-1/2"	7801-150	80	0.19
2"	7801-200	80	0.24
2-1/2"	7801-250	65	0.30
3"	7801-300	80	0.36
4"	7801-400	70	0.53

SIZE (ID)	ITEM NUMBER	PSI RATING	LBS / FOOT
5"	7801-500	40	0.65
6"	7801-600	60	0.87
8"	7801-800	35	1.30
10"	7801-10	35 / 80*	1.90 / 2.15
12"	7801-12	35 / 60*	2.45 / 2.75
14"	7801-14	30	2.70
16"	7801-16	30	3.10

\*10" & 12" ALSO AVAILABLE IN HEAVY GRADE

**PSI RATING LISTED IS THE RECOMMENDED MAX OPERATING PRESSURE OF THE BULK HOSE ONLY  
HOSE ASSEMBLY WORKING PRESSURE RATING IS DEPENDENT ON THE COUPLING TYPE**