

THREADED HOSE COUPLINGS

PIN-LUG THREADED COUPLINGS ALUMINUM WITH BRASS SWIVEL



HOSE SIZE	FEMALE X HOSE	MALE X HOSE	M & F SET	WASHER
1-1/2"	FAB150	MA150	CAB150	KRW150
1-1/2"(NST)	FAB150N	MA150N	CAB150N	KRW2075
2"	FAB200	MA200	CAB200	KRW200
2-1/2"	FAB250	MA250	CAB250	KRW250
2-1/2"(NST)	FAB250N	MA250N	CAB250N	KRW3075
3"	FAB300	MA300	CAB300	KRW300
4"	FAB400	MA400	CAB400	KRW400
6"	FAB600	MA600	CAB600	KRW600

DESIGNED FOR LOW PRESSURE FLUID SERVICE ONLY - NOT FOR AIR SERVICE
ALSO AVAILABLE IN PLATED STEEL, PLATED IRON, & BRASS

NPSH THREAD (NATIONAL PIPE STRAIGHT HOSE THREAD) SEALS ON THE WASHER
FEMALE NPSH THREAD WILL ACCEPT MALE NPT, MALE NPSH WILL NOT FIT INTO FEMALE NPT
FOR NPT COMPATIBLE COUPLING SETS, USE FEMALE PIN-LUG NPSH AND MALE NPT BELOW

COMBINATION (KC) NIPPLES



HOSE SIZE (I.D.)	NPT NIPPLE PLATED STEEL	NPT NIPPLE 316 STAINLESS STEEL	GROOVED NIPPLE STEEL	FIXED FLANGED NIPPLE* STEEL
3/4"	STC5	RST5	-	-
1"	STC10	RST10	STV10	-
1-1/4"	STC15	RST15	STV15	-
1-1/2"	STC20	RST20	STV20	FST20
2"	STC25	RST25	STV25	FST25
2-1/2"	STC30	RST30	STV30	-
3"	STC35	RST35	STV35	FST35
4"	STC40	RST40	STV40	FST40
6"	STC60	RST60	STV60	FST60
8"	STC80	RST80	STV80	FST80
10"	STC100	-	STV100	FST100
12"	STC120	-	STV120	FST120

DESIGNED FOR LOW PRESSURE FLUID SERVICE ONLY - NOT FOR AIR SERVICE
ALSO AVAILABLE IN ALUMINUM, BRASS, & POLYPROPYLENE (SELECT SIZES)
* FLANGE IS 150# ANSI PATTERN - NIPPLE FOR FLOATING FLANGE AVAILABLE