

DISCHARGE HOSE

7801R – RED HD PVC DISCHARGE

ASSEMBLIES WITH MALE & FEMALE NPSH THREADED COUPLINGS



1-1/2" X 50'	7801R-150X50MF*
2" X 50'	7801R-2X50MF
2-1/2" X 50'	7801R-250X50MF*
3" X 50'	7801R-3X50MF
4" X 50'	7801R-4X50MF
6" X 50'	7801R-6X50MF

*SIZES AVAILABLE WITH NST FIRE THREAD

ASSEMBLIES WITH CAM LOCK ALUMINUM QUICK CONNECT COUPLINGS



1-1/2" X 50'	7801R-150X50CE
2" X 50'	7801R-2X50CE
2-1/2" X 50'	7801R-250X50CE
3" X 50'	7801R-3X50CE
4" X 50'	7801R-4X50CE
6" X 50'	7801R-6X50CE

AVAILABLE WITH BALL & SOCKET COUPLINGS

300 FT MAX ROLL LENGTH

BULK HOSE

-5 TO +170 DEG F

SIZE (ID)	ITEM NUMBER	PSI RATING	LBS / FOOT	FULL ROLL LENGTH
1-1/2"	7801R-150	150	0.28	300'
2"	7801R-200	150	0.34	300'
2-1/2"	7801R-250	150	0.40	300'
3"	7801R-300	150	0.55	300'
4"	7801R-400	150	0.85	300'
6"	7801R-600	150	1.34	300'
8"	7801R-800	115	1.90	300'

PSI RATING LISTED IS THE RECOMMENDED MAX OPERATING PRESSURE OF THE BULK HOSE ONLY
HOSE ASSEMBLY WORKING PRESSURE RATING IS DEPENDENT ON THE COUPLING TYPE