

## UNIVERSAL COUPLINGS

**NOT FOR STEAM SERVICE**  
150 MAX PSI



**UNIVERSAL X F NPT**

SIZE (ID)	MAL IRON (USA)	STEEL (IMPR)	316 SS (USA)	BRASS (IMPR)
1/4"	AMC1	GAMC1	-	ABC1
3/8"	AMC	GAMC	RAMC	ABC
1/2"	AM3	GAM3	RAM3	AB3
3/4"	AM8	GAM8	RAM8	AB8
1"	AM13	GAM13	RAM13	AB13
1-1/4"	AM18	GAM18	-	AB18
1-1/2"	AM23	GAM23	-	AB23
2"	AM28	GAM28	-	AB28



**UNIVERSAL X M NPT**

SIZE (ID)	MAL IRON (USA)	STEEL (IMPR)	316 SS (USA)	BRASS (IMPR)
1/4"	AMB1	GAMB1	-	ABB1
3/8"	AMB	GAMB	RAMB	ABB
1/2"	AM2	GAM2	RAM2	AB2
3/4"	AM7	GAM7	RAM7	AB7
1"	AM12	GAM12	RAM12	AB12



**UNIVERSAL X HOSE**

SIZE (ID)	MAL IRON (USA)	STEEL (IMPR)	316 SS (USA)	BRASS (IMPR)
3/8"	AMH	GAMH	RAMH	ABH
1/2"	AM1	GAM1	RAM1	AB1
3/4"	AM6	GAM6	RAM6	AB6
1"	AM11	GAM11	RAM11	AB11
1-1/4"	AM16	GAM16	-	AB16
1-1/2"	AM21	GAM21	-	AB21
2"	AM26	GAM26	-	AB26

SEE CLAMP SECTION FOR BOLTED INTERLOCK CLAMPS



**4-LUG DESIGN (1-1/4" - 2" SIZES)**

NOT INTERCHANGEABLE WITH 2-LUG COUPLINGS

2-LUG GASKET (50 PK)	2-LUG OIL RES GSKT (50 PK)	4-LUG GASKET (EACH)	SAFETY CLIP (25 PK)
AWR4	AWS6	AWR14	AC1

2-LUG TRIPLE CONNECT & BLANK END CAP ALSO AVAILABLE

SWIVEL COUPLINGS AVAILABLE IN 3/4 INCH

ALWAYS USE SAFETY CLIPS (INCLUDED WITH EACH)