

AIR HOSE ACCESSORIES

HOSE SAFETY WHIP CHECK CABLES

DESIGNED FOR 200 PSI AIR HOSE SERVICE



HOSE (ID) RANGE	CABLE DIAMETER	CABLE LENGTH	WIRE MATERIAL	HOSE - HOSE TYPE	HOSE - TOOL TYPE
1/2" - 1-1/4"	1/8"	20.25"	GALV. STEEL	WB1	WSR1
1/2" - 2"	3/16"	28"	GALV. STEEL	WB3	WSR2
1-1/2" - 3"	1/4"	38"	GALV. STEEL	WA2	WSR3
4"	3/8"	44"	GALV. STEEL	WA4	WSR4
1/2" - 1-1/4"	1/8"	20.25"	304 STAINLESS	WB1SS	WSR1SS
1-1/2" - 3"	1/4"	38"	304 STAINLESS	WA2SS	WSR2SS

HOSE TO TOOL TYPE HAS ONE SPRING LOOP END AND ONE WIDE ADJUSTABLE LOOP END

CABLES MUST BE INSTALLED FULLY EXTENDED ACROSS THE HOSE WITH NO SLACK
INSTALLATION WITH THE CABLE LOOP CLOSE TO THE HOSE COUPLING GREATLY INCREASES
THE CHANCE THAT THE PRESSURIZED HOSE MAY BREAK FREE FROM THE RESTRAINT

AIR SAFETY CHECK VALVES

250 MAX PSI • BRASS WITH STAINLESS INTERNAL SPRING
NOT FOR APPLICATIONS WHERE 100% AVAILABLE AIR IS REQUIRED



NPT & HOSE (ID)	CUT OFF RATE (SCFM @ 90PSI)	ITEM NUMBER
3/8"	39 - 47	SCVM3
3/8"	52 - 65	SCVS3
1/2"	70 - 78	SCVM4
1/2"	80 - 96	SCVS4
3/4"	72 - 88	SCVL6
3/4"	92-108	SCVM6

NPT & HOSE (ID)	CUT OFF RATE (SCFM @ 90PSI)	ITEM NUMBER
3/4"	112 - 128	SCVR6
3/4"	132 - 148	SCVJ6
3/4"	160 - 180	SCVS6
3/4"	180 - 200	SCVH6
1"	165 - 195	SCVL8
1"	220 - 260	SCVM8

NPT & HOSE (ID)	CUT OFF RATE (SCFM @ 90PSI)	ITEM NUMBER
1"	280 - 320	SCVS8
1"	310 - 340	SCVH8
1-1/2"	300 - 360	SCVL12
1-1/2"	470 - 530	SCVM12
1-1/2"	640 - 720	SCVS12
1-1/2"	750 - 830	SCVH12

ADDITIONAL SIZES AVAILABLE, PLEASE INQUIRE

IN-LINE OIL LUBRICATORS



ADJUSTABLE FLOW

NPT SIZE	OIL CAPACITY	AIR FLOW (@ 70 PCS)	MAX PSI (@ 70 DEG F)	ITEM NUMBER
1/2"	1.4 FL OZ	30 SCFM	500 PSI	PL300
3/4"	3.7 FL OZ	70 SCFM	200 PSI	PL400
3/4"	11 FL OZ	70 SCFM	300 PSI	PL400L
1"	16 FL OZ	100 SCFM	250 PSI	PL500

INSTALL WITHIN 25 FEET OF THE TOOL • DO NOT USE OIL ADDITIVES
BASE FRAME AVAILABLE TO KEEP UNIT UPRIGHT DURING USE