

DISCHARGE HOSE

3200 / 3220 – MILL DISCHARGE

ASSEMBLIES WITH MALE & FEMALE NPSH THREADED COUPLINGS



1-1/2" X 50'	3200-150X50MF*
2" X 50'	3200-2X50MF
2-1/2" X 50'	3200-250X50MF*
3" X 50'	3200-3X50MF
4" X 50'	3200-4X50MF
6" X 50'	3200-6X50MF

*SIZES AVAILABLE WITH NST FIRE THREAD

ASSEMBLIES WITH CAM LOCK ALUMINUM QUICK CONNECT COUPLINGS



1-1/2" X 50'	3200-150X50CE
2" X 50'	3200-2X50CE
2-1/2" X 50'	3200-250X50CE
3" X 50'	3200-3X50CE
4" X 50'	3200-4X50CE
6" X 50'	3200-6X50CE

**DOUBLE JACKET ASSEMBLIES AVAILABLE
TYPE #3220 (SEE CHART BELOW)**

BULK HOSE 100 FT MAX THROUGH 4 INCH

SINGLE JACKET			
SIZE (ID)	ITEM NUMBER	PSI RATING	LBS / FOOT
1"	3200-100	150	0.16
1-1/2"	3200-150	150	0.20
2"	3200-200	150	0.27
2-1/2"	3200-250	150	0.37
3"	3200-300	150	0.43
4"	3200-400	150	0.62
6"	3200-600	115	1.10

DOUBLE JACKET			
SIZE (ID)	ITEM NUMBER	PSI RATING	LBS / FOOT
1-1/2"	3220-150	300	0.29
2"	3220-200	300	0.40
2-1/2"	3220-250	300	0.50
3"	3220-300	250	0.63
4"	3220-400	250	0.76

NOT RATED FOR FIRE PROTECTION

**PSI RATING LISTED IS THE RECOMMENDED MAX OPERATING PRESSURE OF THE BULK HOSE ONLY
HOSE ASSEMBLY WORKING PRESSURE RATING IS DEPENDENT ON THE COUPLING TYPE**