

DISCHARGE HOSE

9801 – RUBBER DISCHARGE

ASSEMBLIES WITH MALE & FEMALE NPSH THREADED COUPLINGS



1-1/2" X 50'	9801-150X50MF*
2" X 50'	9801-2X50MF
2-1/2" X 50'	9801-250X50MF*
3" X 50'	9801-3X50MF
4" X 50'	9801-4X50MF
6" X 50'	9801-6X50MF

*SIZES AVAILABLE WITH NST FIRE THREAD

ASSEMBLIES WITH CAM LOCK ALUMINUM QUICK CONNECT COUPLINGS



1-1/2" X 50'	9801-150X50CE
2" X 50'	9801-2X50CE
2-1/2" X 50'	9801-250X50CE
3" X 50'	9801-3X50CE
4" X 50'	9801-4X50CE
6" X 50'	9801-6X50CE

**ASSEMBLY NUMBERS SHOWN ARE FOR 2-PLY REINFORCED HOSE
4-PLY REINFORCED HOSE AVAILABLE, # 9801H (SEE CHART BELOW)**

AVAILABLE WITH BALL & SOCKET COUPLINGS

100 FT MAX LENGTH TO 10"

BULK HOSE

-25 TO +180 DEG F

SIZE (ID)	ITEM NUMBER	2-PLY PSI RATING	4-PLY PSI RATING	SIZE (ID)	ITEM NUMBER	2-PLY PSI RATING	4-PLY PSI RATING
1-1/2"	9801_-150	150	250	5"	9801_-500	150	200
2"	9801_-200	150	250	6"	9801_-600	100	150
2-1/2"	9801_-250	150	250	8"	9801_-800	100	125
3"	9801_-300	150	225	10"	9801_-10	100	125
4"	9801_-400	150	200	12"	9801_-12	100	125

LARGE DIAMETER HOSE & ABRASION RESISTANT TUBE MATERIALS AVAILABLE

NOT RECOMMENDED FOR SAND, GRAVEL, OR CEMENT DISCHARGE APPLICATIONS

**PSI RATING LISTED IS THE RECOMMENDED MAX OPERATING PRESSURE OF THE BULK HOSE ONLY
HOSE ASSEMBLY WORKING PRESSURE RATING IS DEPENDENT ON THE COUPLING TYPE**