

DISCHARGE HOSE

9821 – NITRILE RUBBER DISCHARGE

ASSEMBLIES WITH CAM LOCK ALUMINUM QUICK CONNECT COUPLINGS



ALSO AVAILABLE
IN BLACK COVER

1-1/2" X 50'	9821-150X50CE
2" X 50'	9821-2X50CE
2-1/2" X 50'	9821-250X50CE
3" X 50'	9821-3X50CE
4" X 50'	9821-4X50CE
6" X 50'	9821-6X50CE

ADDITIONAL CONFIGURATIONS AVAILABLE

AVAILABLE WITH BALL & SOCKET COUPLINGS

ASSEMBLIES WITH ROCKER LUG ANODIZED ALUMINUM M&F COUPLINGS



ANODIZED ALUMINUM
FULL FLOW COUPLINGS

HOSE SIZE (ID)	THREAD TYPE	ITEM NUMBER
1-1/2" X 50'	NPSH	9821-150X50MFRL
1-1/2" X 50'	NST	9821-150X50NSTRL
2" X 50'	NPSH	9821-2X50MFRL
2-1/2" X 50'	NPSH	9821-250X50MFRL
2-1/2" X 50'	NST	9821-250X50NSTRL
3" X 50'	NPSH	9821-3X50MFRL

250 PSI / 500 TEST STANDARD, 300 PSI / 600 TEST AVAILABLE
4", 5", & 6" AVAILABLE IN NST OR STORZ QUICK CONNECT

100 FT MAX ROLL LENGTH

BULK HOSE

-20 TO +210 DEG F

ALSO AVAILABLE
BY CUSTOM ORDER:

ADDITIONAL COLORS
URETHANE VERSION
300 & 660 FT LENGTHS
(MINIMUM MAY APPLY)

SIZE (ID)	ITEM NUMBER	PSI RATING	LBS / FOOT
1-1/2"	9821-150	250	0.26
2"	9821-200	250	0.35
2-1/2"	9821-250	250	0.47
3"	9821-300	250	0.65
4"	9821-400	200	0.85
6"	9821-600	150	1.60
8"	9821-800	150	2.30

REUSABLE COUPLINGS
AVAILABLE UP TO 12"



GROOVED OR THREADED
ANODIZED ALUMINUM

PSI RATING LISTED IS THE RECOMMENDED MAX OPERATING PRESSURE OF THE BULK HOSE ONLY
HOSE ASSEMBLY WORKING PRESSURE RATING IS DEPENDENT ON THE COUPLING TYPE