

8702 – STEAM HOSE



**INSPECT, MAINTAIN, & REPLACE
STEAM HOSE ASSEMBLIES REGULARLY**

ASSEMBLIES WITH FEMALE GROUND JOINT COUPLINGS SPUD ADAPTERS NOT INCLUDED

1/2" X 50'	8702-50X50FSGJ
3/4" X 50'	8702-75X50FSGJ
1" X 50'	8702-1X50FSGJ
1-1/4" X 50'	8702-125X50FSGJ
1-1/2" X 50'	8702-150X50FSGJ
2" X 50'	8702-2X50FSGJ

ASSEMBLIES WITH MALE NPT & FEMALE GROUND JOINT COUPLINGS

1/2" X 50'	8702-50X50MFGJ
3/4" X 50'	8702-75X50MFGJ
1" X 50'	8702-1X50MFGJ
1-1/4" X 50'	8702-125X50MFGJ
1-1/2" X 50'	8702-150X50MFGJ
2" X 50'	8702-2X50MFGJ

ASSEMBLIES WITH MALE NPT COUPLING EACH END

1/2" X 50'	8702-50X50MM
3/4" X 50'	8702-75X50MM
1" X 50'	8702-1X50MM
1-1/4" X 50'	8702-125X50MM
1-1/2" X 50'	8702-150X50MM
2" X 50'	8702-2X50MM

ALWAYS USE SAFETY CABLES TO SECURE STEAM HOSE

ASSEMBLIES AVAILABLE IN OTHER LENGTHS AND COUPLING CONFIGURATIONS

100 FT MAX ROLL THROUGH 2"

BULK HOSE

**406 DEG F SATURATED /
450 DEG F SUPER-HEATED**

SIZE (ID)	ITEM NUMBER	PSI RATING	LBS / FOOT
1/2"	8702-50	250	0.50
3/4"	8702-75	250	0.65
1"	8702-100	250	0.85
1-1/4"	8702-125	250	1.20

SIZE (ID)	ITEM NUMBER	PSI RATING	LBS / FOOT
1-1/2"	8702-150	250	1.40
2"	8702-200	250	1.80
3"	8702-300	250	3.20

**FLEXIBLE STAINLESS STEEL HOSE
ASSEMBLIES FOR STEAM USE AVAILABLE**

THE TEMPERATURE OF STEAM WILL INCREASE AS PRESSURE ELEVATES
ALWAYS AVOID KINKS, TWISTS, AND TIGHT BENDS IN INSTALLATION AND SERVICE
ALWAYS DEPRESSURIZE AND DRAIN STEAM HOSE ASSEMBLY WHEN NOT IN SERVICE

WARNING: ONLY USE APPROVED COUPLINGS AND COMPONENTS FOR STEAM SERVICE