

5809 – CONCRETE / PLASTER GROUT

ASSEMBLIES WITH FULL-FLOW GROOVED COUPLINGS



1-1/2" X 50'	5809-150X50V
2" X 50'	5809-2X50V

25 FOOT LENGTHS ALSO AVAILABLE

ASSEMBLIES WITH FULL-FLOW HD RAISED COUPLINGS



1-1/2" X 50'	5809-150X50H
2" X 50'	5809-2X50H
2-1/2" X 50'	5809-250X50H
3" X 50'	5809-3X50H
4" X 50'	5809-4X50H

25 FOOT LENGTHS ALSO AVAILABLE

HD SNAP CLAMPS

HOSE SIZE	GROOVED (ORANGE)	HD RAISED (GREEN)
1-1/2"	C15SG	C15SD
2"	C20SG	C20SD
2-1/2"	-	C25SD
3"	-	C30SD



SIZES 3" AND UP ARE ADJUSTABLE

REDUCERS & THREADED ADAPTERS ALSO AVAILABLE

100 FT MAX ROLL LENGTH

BULK HOSE

-40 TO +200 DEG F

SIZE (ID)	ITEM NUMBER	PSI RATING*	BEND RADIUS	LBS / FOOT
1-1/4"	5809-125	800	8"	0.88
1-1/2"	5809-150	800	10"	0.95
2"	5809-200	800	12"	1.50
2-1/2"	5809-250	600	14"	1.75
3"	5809-300	600	15"	2.50
4"	5809-400	600	18"	4.10

WIRE BRAIDED HOSE ASSEMBLIES ALSO AVAILABLE

PSI RATING LISTED IS FOR ASSEMBLED HOSE WITH CRC INSTALLED INTERNAL EXPANSION COUPLINGS
 BULK HOSE IS RATED AT 170 BAR BURST, WITH 2:1 WORKING PRESSURE RATING PER ASME B30.27-2009
 ADDITIONAL STYLES AND DIAMETERS AVAILABLE - PLEASE INQUIRE