

5601 – SANDBLAST HOSE



ASSEMBLIES WITH ALUMINUM QUICK-CONNECT EACH END

3/4" X 50'	5601-75X50QC
1" X 50'	5601-1X50QC
1-1/4" X 50'	5601-125X50QC
1-1/2" X 50'	5601-150X50QC

ALSO AVAILABLE WITH THREADED NOZZLE HOLDER

SANDBLAST HOSE COUPLINGS

SHOWN IN ALUMINUM, BRASS COUPLINGS AVAILABLE

SIZE	HOSE QUICK COUPLING	HOSE NOZZLE HOLDER	THREADED QUICK COUPLING
3/4"	ASB75	ANH75	-
1"	ASB100	ANH100	-
1-1/4"	ASB125	ANH125	ASC125
1-1/2"	ASB150	ANH150	ASC150



SANDBLAST COUPLINGS INTERCONNECT BETWEEN ALL SIZES
NOZZLE HOLDER COUPLINGS ARE 1-1/4" FEMALE THREAD

SANDBLAST COUPLINGS DO NOT INTERCHANGE WITH UNIVERSAL AIR COUPLINGS

DISTANCE BETWEEN THE LUGS: (APPROXIMATE)

SANDBLAST: 2.20" - UNIVERSAL 2-LUG: 1.60" - UNIVERSAL 4-LUG: 2.60"

ALWAYS USE SAFETY CABLES TO SECURE SANDBLAST HOSE

100 FT MAX ROLL LENGTH

BULK HOSE

-25 TO +185 DEG F

SIZE (ID)	OUTSIDE DIAMETER	ITEM NUMBER	PSI RATING	LBS / FOOT
1/2"	SEE NOTE	5601-50	150	0.35
3/4"	1.50	5601-75	150	0.66
1"	1.88	5601-100	150	0.80
1-1/4"	2.16	5601-125	150	1.05
1-1/4"*	1.88	5601L-125	150	0.85
1-1/2"	2.38	5601-150	150	1.25
2"*	2.88	5601-200	150	1.45

1/2" DIAMETER SANDBLAST HOSE IS AVAILABLE IN 1", 1-1/16", & 1-1/8" OD
5601L-125 HOSE IS DESIGNED TO BE USED WITH 1" SANDBLAST COUPLINGS
ONLY USE HOSE DESIGNATED FOR SANDBLAST SERVICE AND PROPERLY MATCHED COUPLINGS