

# TUBING PRODUCTS

## 8601 – BRAIDED PVC TUBING



**-10 TO +130 (DEG F) SERVICE TEMPERATURE**

**NON-TOXIC FDA / USDA COMPLIANT MATERIAL**

**HEAVY WALL VERSION AVAILABLE IN SELECT SIZES**

**INCREASED PRESSURE VS. NON-REINFORCED TUBING**

**ASSEMBLIES AVAILABLE IN A VARIETY OF CONFIGURATIONS**

### CUSTOM MANUFACTURED OPTIONS INCLUDE:

- SPECIAL WALL THICKNESS AND HARDNESS (DUROMETER)
- CUSTOM COLORS AND TINTS, INCLUDING TRACER YARNS
- CUSTOM LENGTHS & NON COILED LENGTHS (NO CURVE)

**NSF51-61 RATED TUBING AVAILABLE BY SPECIAL REQUEST (FULL ROLLS ONLY)**

**ADDITIONAL MATERIALS INCLUDING URETHANE, EVA, AND SILICONE AVAILABLE**

SIZE ID:	SIZE OD:	ITEM NUMBER	PSI RATING (@ 70 deg F)	LBS / FT	COIL LENGTH (FT)
1/8	5/16	8601-12	250	0.04	300
3/16	13/32	8601-18	250	0.06	300
1/4	15/32	8601-25	250	0.07	300
5/16	17/32	8601-31	250	0.08	300
3/8	5/8	8601-38	200	0.11	300
1/2	3/4	8601-50	200	0.13	300
5/8	7/8	8601-63	200	0.15	200
3/4	1-1/32	8601-75	175	0.20	300
1	1-5/16	8601-100	125	0.32	100
1-1/4	1-3/4	8601-125	100	0.63	100
1-1/2	2	8601-150	75	0.75	100
2	2-1/2	8601-200	75	0.95	100

**FULL ROLL PURCHASE REQUIRED IN SOME SIZES**

**PSI RATING LISTED IS THE RECOMMENDED MAX OPERATING PRESSURE OF THE BULK HOSE ONLY  
HOSE ASSEMBLY WORKING PRESSURE RATING IS DEPENDENT ON THE COUPLING TYPE**