

HOBBLE CLAMP RANGE*	2-Bolt Double Eye Clamp Number:	2-Bolt Single Eye Clamp Number:	4-Bolt Double Eye Clamp Number:	4-Bolt Single Eye Clamp Number:	APPROX WEIGHT** (LBS)
5/8" - 7/8"	2BDE-075	-	-	-	1.35
7/8" - 1-1/8"	2BDE-100	-	-	-	1.50
1-1/8" - 1-3/8"	2BDE-125	-	-	-	1.60
1-3/8" - 1-5/8"	2BDE-150	-	-	-	1.65
1-45/64" - 2-3/8"	2BDE-196	2BSE-196	-	-	4.05
2-1/8" - 2-1/2"	2BDE-238	-	4BDE-238	-	4.85
2-3/8" - 2-5/8"	2BDE-263	2BSE-263	4BDE-263	-	4.85
2-13/16" - 3-1/4"	2BDE-300	2BSE-300	4BDE-300	-	5.00
3-1/4" - 3-5/8"	2BDE-350	2BSE-350	4BDE-350	-	5.50
3-45/64" - 4-1/8"	2BDE-400	2BSE-400	4BDE-400	-	5.75
4-1/4" - 4-5/8"	2BDE-450	2BSE-450	4BDE-450	4BSE-450	11.00
4-3/4" - 5-1/4"	2BDE-500	2BSE-500	4BDE-500	4BSE-500	12.00
5-5/16" - 5-5/8"	2BDE-550	2BSE-550	4BDE-550	4BSE-550	12.25
5-45/64" - 6-1/4"	2BDE-600	2BSE-600	4BDE-600	4BSE-600	14.35
6-5/16" - 6-3/4"	2BDE-650	2BSE-650	4BDE-650	4BSE-650	15.50
6-13/16" - 7-1/4"	2BDE725	2BSE-725	4BDE-725	4BSE-725	17.25
7-13/16" - 8-1/2"	2BDE800	2BSE-800	4BDE-800	4BSE-800	19.00

2BDE = 2 BOLT 4BDE = 4 BOLT DE = DOUBLE EYE SE = SINGLE EYE

***Hose Outside Diameter must fit with clamp range, (do not order based on hose ID)**

A properly sized clamp should have a gap when installing. If two clamp halves are touching, it is too large for the hose.

Torque bolts to 60 Ft Lbs. Check and retension regularly. Install 12 inches from end of coupling ferrule or hose clamp.

Clamps are made from electrostatically powder coated carbon steel (width & thickness vary by size)

*** Weight is based on 2 bolt double eye hobble clamp. Use only as a rough guide for estimation*